

## MIRROR

### MIR 600 ONE-WAY MIRROR

#### INDOOR INSTALLATION



See without being seen

#### HIGH PERFORMANCE ONE-WAY MIRROR

##### DESCRIPTION

**HIGH PERFORMANCE.** The principle of a measured metallization of the polyester support forms a reflective screen in daylight, which reflects the image like a mirror. All this while preserving the transparency and visual properties of the glass on the inside. The user can see without being seen. The application of a one-way mirror film effectively solves the delicate problem of large glass surfaces, when they allow prying eyes.



**Durability:** 12 to 15 years for a vertical application in Central Europe.



**Use:** For clear glass and double glazing smaller than 1.20 m<sup>2</sup>.



**Maintenance :** after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



**Storage:** 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions

#### INFORMATION

**MATERIAL :** .....PET  
**ADHESIVE :** .....Acrylic polymer 25 gr/m<sup>2</sup>  
**LINER :** .....Siliconized PET 23 microns  
**THICKNESS :** .....60 microns  
**COLOR :** .....Silver  
**APPLICATION SIDE :** .....Internal  
**TRANSMISSION UVA :** .....5,9%  
**APPLICATION T° :** .....min, + 5°C  
**STANDARDS :** .....EUROCLASSES  
**FIRE RANTING :** ..... B-s1,d0  
**GUARANTEE :** .....10 Years inside\*

\* For glazing not exposed to the sun

#### DIMENSIONS

By roll :



1,52 x  
10 m  
30 m

Application  
Note



Video of the  
installation



##### Method of application

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

##### Production monitoring and standards

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.