

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 15-6-2012 Revision date: 9-5-2023 Supersedes version of: 3-9-2019 Version: 4.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: CS100 INK BLACK
UFI	: AVMS-FC2V-T40A-HPY4
Product code	: CS100-K-BB
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category

: Industrial use, Professional use

Title	Use descriptors
CS100 INK BLACK	SU0, PC18, PROC1

Full text of use descriptors: see section 16

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Mimaki Europe B.V. Stammerdijk 7E 1112 AA Diemen Netherlands T +31 20 4627640 reach@mimakieurope.com

1.4. Emergency telephone number

Emergency number

: National Poisons Information Centre +31 (0)30 - 274 8888 (Only for the purpose of informing medical personnel in cases of accidental intoxications. The emergency phone number is 24 hours/day available.)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

H318

H336

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 1 Specific target organ toxicity - Single exposure, Category 3, Narcosis Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) N	lo. 1272/2008 [CLP]
Hazard pictograms (CLP)	
	GHS05 GHS07
Signal word (CLP)	: Danger
Contains	: y-Butyrolactone; 2-methoxy-1-methylethyl acetate
Hazard statements (CLP)	: H318 - Causes serious eye damage. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	 P261 - Avoid breathing vapours, mist. P280 - Wear eye protection, face protection. P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. P312 - Call a POISON CENTRE or doctor if you feel unwell. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% w/w (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-butoxyethyl acetate; butylglycol acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 112-07-2 EC-No.: 203-933-3 EC Index-No.: 607-038-00-2 REACH-no: 01-2119475112- 47	≥ 50	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312
γ-Butyrolactone	CAS-No.: 96-48-0 EC-No.: 202-509-5 REACH-no: 01-2119471839- 21	10 – 30	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 STOT SE 3, H336
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791- 29	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336
Carbon black substance with national workplace exposure limit(s) (GB)	CAS-No.: 1333-86-4 EC-No.: 215-609-9 REACH-no: 01-2119384822- 32	1 – 5	Not classified

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If irritation persists, consult a doctor.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: Rinse mouth. Give water to drink. Do NOT induce vomiting. Seek medical attention if ill effect develops.
4.2. Most important symptoms and effects	, both acute and delayed
Symptoms/effects after inhalation Symptoms/effects after eye contact	May cause drowsiness or dizziness.Causes serious eye damage.
4.3. Indication of any immediate medical at	tention and special treatment needed
No additional information available	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Alcohol resistant foam. Water spray. Dry powder. Carbon dioxide.Heavy water stream.
5.2. Special hazards arising from the subst	ance or mixture
Hazardous decomposition products in case of fire	: Oxidizing agent.
5.3. Advice for firefighters	
Precautionary measures fire Firefighting instructions	 Eliminate ignition sources. Keep upwind. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Combustible.

: Combustible.

SECTION 6: Accidental release measures		
6.1. Personal precautions, protec	tive equipment and emergency procedures	
General measures	: Remove ignition sources. Provide adequate ventilation.	
6.1.1. For non-emergency personnel		
Protective equipment	: Equip cleanup crew with proper protection.	
Emergency procedures	: Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing vapours, mist.	
Emergency procedures	: Keep public away from danger area. Ventilate area.	
6.2. Environmental precautions		

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for con	tainment and cleaning up
Methods for cleaning up	 Clean up any spills as soon as possible, using an absorbent material to collect it. Do not use Sawdust. Sweep or shovel spills into appropriate container for disposal. Store away from other materials.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Good ventilation of the workplace required. Use grounded electrical/mechanical equipment Containers must be properly grounded before beginning transfer. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapours, mist. If skin contact or contamination of clothing is possible, protective clothing should be worn. Face shield. Wash hands and other exposed areas with mild soap and water before eating drinking or smoking and when leaving work.
7.2. Conditions for safe storage, including	g any incompatibilities
Storage conditions	 Keep cool. Store in a dry place. Keep only in the original container in a cool well ventilated place. Keep container tightly closed. Strong bases. Strong acids.
Incompatible materials Information on mixed storage	 Sources of ignition. Direct sunlight. Oxidation agents. Strong alkalis.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values	

2-butoxyethyl acetate; butylglycol acetate (112-07-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	2-Butoxyethyl acetate	
IOEL TWA	133 mg/m ³	
IOEL TWA [ppm]	20 ppm	
IOEL STEL	333 mg/m ³	
IOEL STEL [ppm]	50 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	2-Butoxyethyl acetate	
WEL TWA (OEL TWA) [1]	133 mg/m ³	
WEL TWA (OEL TWA) [2]	20 ppm	
WEL STEL (OEL STEL)	332 mg/m ³	
WEL STEL (OEL STEL) [ppm]	50 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethyl acetate; butylglycol acetate (11	2-07-2)
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL))
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	550 mg/m³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	·
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA) [1]	274 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	548 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Carbon black (1333-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Carbon black
WEL TWA (OEL TWA) [1]	3,5 mg/m ³
WEL STEL (OEL STEL)	7 mg/m³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

2-butoxyethyl acetate; butylglycol acetate (112-07-2)		
DNEL/DMEL (Workers)		
Acute - systemic effects, dermal 120 mg/kg bodyweight/day		
Acute - local effects, inhalation	333 mg/m ³	
Long-term - systemic effects, dermal	169 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	133 mg/m³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethyl acetate; butylglycol acetate (1	2-butoxyethyl acetate; butylglycol acetate (112-07-2)		
DNEL/DMEL (General population)			
Acute - systemic effects, dermal	72 mg/kg bodyweight/day		
Acute - systemic effects, oral	36 mg/kg bodyweight/day		
Acute - local effects, inhalation	200 mg/m ³		
Long-term - systemic effects,oral	8,6 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	80 mg/m ³		
Long-term - systemic effects, dermal	102 mg/kg bodyweight/day		
PNEC (Water)			
PNEC aqua (freshwater)	0,304 mg/l		
PNEC aqua (marine water)	0,0304 mg/l		
PNEC aqua (intermittent, freshwater)	0,56 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	2,03 mg/kg dwt		
PNEC sediment (marine water)	0,203 mg/kg dwt		
PNEC (Soil)			
PNEC soil	0,415 mg/kg dwt		
PNEC (Oral)			
PNEC oral (secondary poisoning)	60 mg/kg food		
PNEC (STP)			
PNEC sewage treatment plant	90 mg/l		
γ-Butyrolactone (96-48-0)			
DNEL/DMEL (Workers)			
Acute - systemic effects, inhalation	958 mg/m³		
Long-term - systemic effects, dermal	19 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	130 mg/m ³		
PNEC (Water)			
PNEC aqua (freshwater)	0,056 mg/l		
PNEC aqua (marine water)	0,0056 mg/l		
PNEC aqua (intermittent, freshwater)	0,56 mg/l		
PNEC (Sediment)	PNEC (Sediment)		
PNEC sediment (freshwater)	0,24 mg/kg dwt		
PNEC sediment (marine water)	0,02 mg/kg dwt		
PNEC (Soil)			
PNEC soil	0,014683 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	452 mg/l		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-methoxy-1-methylethyl acetate (108-65-6)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	550 mg/m³	
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	275 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, oral	500 mg/kg bodyweight/day	
Long-term - systemic effects,oral	36 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	33 mg/m ³	
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day	
Long-term - local effects, inhalation	33 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0,635 mg/l	
PNEC aqua (marine water)	0,0635 mg/l	
PNEC aqua (intermittent, freshwater)	6,35 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3,29 mg/kg dwt	
PNEC sediment (marine water)	0,329 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,29 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure that there is a suitable ventilation system.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure. Safety glasses. Face shield. Gloves. Wear respiratory protection.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses (acc. EN 166)

8.2.2.2. Skin protection

Skin and body protection:

Where contact with eyes or skin is likely, wear suitable protection. Standard. EN 13034

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Wear suitable gloves resistant to chemical penetration. Protective gloves made of PVA. Breakthrough time (EN 374-3:2003): > 480 min (www.echa.europa.eu). Layer thickness : No data available. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

8.2.2.3. Respiratory protection

Respiratory protection:

Do not inhale vapour. Supplied air respirator if working in a confined area. Approved organic vapour respirator. Type A - High-boiling (>65 °C) organic compounds

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Black.
Odour	: Solvent.
Odour threshold	: Not available
Melting point	: <-30 °C
Freezing point	: Not available
Boiling point	: 145 – 209 °C
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 65 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
рН	: Not available
Viscosity, kinematic	: 4,02 mm²/s
Viscosity, dynamic	: 4 mPa·s
Solubility	: Dispersible.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0,493 kPa (20°)
Vapour pressure at 50°C	: Not available
Density	: 0,995 (25°C)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information	with reg	gard to	physical	hazard	classes	

No additional information available

9.2.2. Other safety characteristics

VOC content : 91 %

SECTION 10: Stability and reactivity	
--------------------------------------	--

10.1. Reactivity

Stable under normal conditions.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Extremely high or low temperatures. Ignition sources. Direct sunlight. Sparks. Open flame. Moisture.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Toxic gases. fume. Carbon dioxide.

SECTION 11: Toxicological information			
11.1. Information on hazard classes as defined	d in Regulation (EC) No 1272/2008		
Acute toxicity (dermal)	Not classified Not classified Not classified		
2-butoxyethyl acetate; butylglycol acetate (112-07-2)			
LD50 oral rat	≈ 1880 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:		
LD50 dermal rabbit	≈ 1500 mg/kg bodyweight Animal: rabbit, Remarks on results: other:		
LC50 Inhalation - Rat	3,91 mg/l (8 h)		
γ-Butyrolactone (96-48-0)			
LD50 oral rat	1582 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)		
LC50 Inhalation - Rat	> 5,1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)		
Soybean oil, expoxidized (8013-07-8)			
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)		
2-methoxy-1-methylethyl acetate (108-65-6)			
LD50 oral rat	6190 mg/kg		
LD50 dermal rat	> 2000 mg/kg bw/day		
Carbon black (1333-86-4)			
LD50 oral rat	> 8000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)		
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:, Guideline: other:, Guideline: other:, Guideline: other:		
LC50 Inhalation - Rat	> 4,6 mg/m³		
Skin corrosion/irritation:Additional information:Serious eye damage/irritation:Respiratory or skin sensitisation:Additional information:Germ cell mutagenicity:Additional information:	Not classified Based on available data, the classification criteria are not met Causes serious eye damage. Not classified Based on available data, the classification criteria are not met Not classified Based on available data, the classification criteria are not met		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carcinogenicity Additional information	 Not classified Based on available data, the classification criteria are not met
γ-Butyrolactone (96-48-0)	
NOAEL (chronic, oral, animal/male, 2 years)	225 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:NTP Protocol, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	450 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:NTP Protocol, Remarks on results: other:Effect type: carcinogenicity (migrated information)
Reproductive toxicity Additional information STOT-single exposure	 Not classified Based on available data, the classification criteria are not met May cause drowsiness or dizziness.
γ-Butyrolactone (96-48-0)	
STOT-single exposure	May cause drowsiness or dizziness.
2-methoxy-1-methylethyl acetate (108-65-6)	1
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure Additional information	Not classified Based on available data, the classification criteria are not met
2-butoxyethyl acetate; butylglycol acetate (1	12-07-2)
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	31 – 62,5 ppm
γ-Butyrolactone (96-48-0)	
NOAEL (oral, rat, 90 days)	225 – 450 mg/kg bodyweight/day
Soybean oil, expoxidized (8013-07-8)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-methoxy-1-methylethyl acetate (108-65-6)	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight/day
LOAEL (dermal, rat/rabbit, 90 days)	3676 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	1000 – 1838 mg/kg bodyweight/day
NOAEC (inhalation, rat, vapour, 90 days)	1000 ppm
Carbon black (1333-86-4)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0,0071 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0,0011 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard Additional information	 Not classified Based on available data, the classification criteria are not met
CS100 INK BLACK	
Viscosity, kinematic	4,02 mm²/s

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethyl acetate; butylglycol acetate (112-07-2)		
Viscosity, kinematic	1,303 – 3,063 mm²/s	
γ-Butyrolactone (96-48-0)		
Viscosity, kinematic	1,77 mm²/s	
2-methoxy-1-methylethyl acetate (108-65-6)		
Viscosity, kinematic	1,23 mm²/s @ 20°C	
11.2. Information on other hazards		

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and	: Based on available data, the classification criteria are not met
symptoms	

SECTION 12: Ecological information		
12.1. Toxicity		
Hazardous to the aquatic environment, short-term : Not classified (acute)		
Hazardous to the aquatic environment, long-term : (chronic)	Not classified	
2-butoxyethyl acetate; butylglycol acetate (11	2-07-2)	
LC50 - Fish [1]	20 – 40 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 - Crustacea [1]	37 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	1570 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	520 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
γ-Butyrolactone (96-48-0)		
LC50 - Fish [1]	56 mg/l Test organisms (species): Lepomis macrochirus	
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
LOEC (acute)	< 7,81 mg/l 72h	
NOEC (acute)	> 18 mg/l 96h	
2-methoxy-1-methylethyl acetate (108-65-6)		
LC50 - Fish [1]	130 mg/l	
EC50 - Crustacea [1]	408 mg/l	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	1000 mg/l	
LOEC (acute)	> 1000 mg/l 96h	
NOEC (acute)	≥ 1000 mg/l 96h	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-methoxy-1-methylethyl acetate (108-65-6)			
NOEC (chronic)	47,5 mg/l (14 d)		
NOEC chronic fish	47,5 mg/l		
NOEC chronic crustacea	100 mg/l (21 d)		
NOEC chronic algae	1 g/l (4 d)		
Carbon black (1333-86-4)			
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	> 10000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
EC50 72h - Algae [2]	> 10000 mg/l Test organisms (species):		
12.2. Persistence and degradability			
CS100 INK BLACK			
Persistence and degradability	Not established.		
Carbon black (1333-86-4)			
Persistence and degradability	Not established.		
12.3. Bioaccumulative potential			
CS100 INK BLACK			
Bioaccumulative potential	Not established.		
2-butoxyethyl acetate; butylglycol acetate (112-07-2)		
Partition coefficient n-octanol/water (Log Pow)	1,51 @ 25°C and pH 7		
γ-Butyrolactone (96-48-0)			
Bioconcentration factor (BCF REACH)	3,16		
Partition coefficient n-octanol/water (Log Pow)	-0,566 @ 25 °C and pH 6 - 8		
2-methoxy-1-methylethyl acetate (108-65-6)			
Partition coefficient n-octanol/water (Log Pow)	1,2 @ 20 °C and pH 6.8		
Carbon black (1333-86-4)			
Bioaccumulative potential	Not established.		
12.4. Mobility in soil			
No additional information available			
12.5. Results of PBT and vPvB assessment			
No additional information available			
12.6. Endocrine disrupting properties			
No additional information available			
12.7. Other adverse effects			
Additional information	: Avoid release to the environment.		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations			
13.1. Waste treatment methods			
Regional legislation (waste) Product/Packaging disposal recommendations	 Disposal must be done according to official regulations. Prevent entry to sewers and public waters. Dispose of this material and its container at hazardous or special waste collection point. Dispose in a safe manner in accordance with local/national regulations. 		
Ecology - waste materials European List of Waste (LoW) code HP Code	 Avoid release to the environment. 08 03 12* - waste ink containing dangerous substances HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. 		

SECTION 14: Transport information

ADR	IMDG IATA		ADN	RID
4.1. UN number or ID r	number	· · · · · · · · · · · · · · · · · · ·		
Not regulated	Not regulated Not regulated Not regulated		Not regulated	
4.2. UN proper shippin	ig name	· · · · · ·		
Not regulated	Not regulated Not regulated		Not regulated	Not regulated
4.3. Transport hazard	class(es)			
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
4.4. Packing group		·	·	
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental ha	zards	·	·	
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

14.6. Special precautions for user

Overland transport Not regulated

Transport by sea Not regulated

Air transport Not regulated

Inland waterway transport Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	2-methoxy-1-methylethyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	CS100 INK BLACK ; 2- butoxyethyl acetate; butylglycol acetate ; γ- Butyrolactone ; 2- methoxy-1-methylethyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content

: 91 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section Changed item Change Comments			
	Revision date	Modified	
	Supersedes	Modified	
2.2	Precautionary statements (CLP)	Modified	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
8.2	Personal protective equipment	Modified	
13.1	H code	Added	

Abbreviations and ac	ronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
IARC	International Agency for Research on Cancer	
EC50	Median effective concentration	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
РВТ	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
STP	Sewage treatment plant	
TLM	Median Tolerance Limit	
SDS	Safety Data Sheet	
vPvB	Very Persistent and Very Bioaccumulative	

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal) Acute toxicity (dermal), Category 4		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral) Acute toxicity (oral), Category 4		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Flam. Liq. 3	Flammable liquids, Category 3	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H312	Harmful in contact with skin.	
H318	Causes serious eye damage.	
H332	Harmful if inhaled.	
H336	May cause drowsiness or dizziness.	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Full text of use descriptors			
PC18	C18 Ink and Toners		
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions			
SU0 Other			

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Eye Dam. 1 H318 Calculation method			
STOT SE 3	H336	Calculation method	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.