

# CAD-COLOR® SUPERTEK™ SUBLISTOP 2.0



## PRINTABLE, DYE-BLOCKING POLYURETHANE FILM

The first ever subli block material offering four way stretch! Utilising the patented STiX<sup>2</sup>™ charcoal-based adhesive. Applied quickly at low temperatures to eliminate heat press marks. Has a lightweight feel on the garment, with a soft touch. Will adhere to virtually all fabrics.



## AVAILABLE IN

50 cm x 25 m rolls

## RECOMMENDED FABRICS

- 100% cotton
- 100% polyester\*
- Polyester-cotton blends
- Lycra® / spandex blends
- Most nylon garments\*

\* Test before application!

## CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as your blade ages. Cutting too deep will result in weeding or printing difficulties.

## APPLICATION INSTRUCTIONS

- Temperature: 150° C
- Time: 5 sec.
- Pressure: medium
- (#4-6 on Hotronix®)
- Peel: warm
- Repress: 5 sec.

## ACCESSORIES RECOMMENDED

- CAD-COLOR® Magic Mask Plus
- Grip Cover Sheet
- Coversheet - Non-Sticky
- EZ Weeder®
- Squeegee

## CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Dry at normal dryer settings on household machines. Do not dry clean. Iron only inside out.

## STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

## DETAILS



## KEY

