



Acrysol

A high quality solvent for cleaning a variety of surfaces.



Features

- Pure “Virgin” solvent
- All purpose body solvent which removes uncured sealers, waxes, greases & adhesives
- Removes silicones
- Very fast drying
- Highly refined product

Benefits

- Leaves no oily film, or residues
- Reduced inventory
- Prevents “Fish Eye”, fewer customer complaints
- Saves time
- No residual odours

Part No.	Description	Packaging
83925	1L	Tin
83930	500ml	Aerosol
83940	25L	Can
83945	200L	Barrel

Application

Preparation is key to successful results in many workshop practices, particularly when working with either paint or adhesive. Acrysol is designed to thoroughly clean and degrease surfaces, before flashing off and leaving a perfectly clean and contamination free surface that is ideal for painting or adhering to. It is a must if there is silicone present on a panel shortly to be painted, or if high strength tape is to be used.

It is safe to use on most surfaces without damaging whilst still having enough cleaning power to remove any residue. Acrysol is also suitable for removing transit waxes from new vehicles.

Instructions

1. Spray/apply Acrysol onto the surface to be treated.
2. Wipe with a clean dry cloth / allow to flash off
3. Repeat if necessary.



Technical Information

Part N°:	83930 / 83925 / 83940 / 83945	Odour:	Strong white spirit/solvent odour
Description:	Acrysol 500ml;1L; 25L; 200L	Temperature Range:	-20 to +35°C
Shelf Life:	30months	Solubility in Water:	No
Selling Unit:	EA	Flash Point:	< 6° C
VOC:	746g/l aerosol 796 g/l bulk liquid	Specific Gravity:	0.796 g/ml Bulk / 0.746g/ml Aerosol
Stock Code:	SAB/ABS//ABS25L/ABS200L		
Customs Tariff			
Code:	3405 3000		
SDS:	Yes		
Consistency:	Low viscosity clear liquid		
Application:	Apply with a clean cloth		
Removal:	Wipe off excess with dry cloth / allow to flash off		



SDS available on www.kenturope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US
Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.
For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenturope.com

Rev: 03/11/16